

ALLOC®

Classics

BRINGS THE LOOK AND FEEL OF CLASSIC WOOD TO LAMINATE FLOORING.

8mm Alloc Classics are 8mm thick and feature exceptional designs.

ALLOC
Herringbone



- Unique mechanical locking system
- Allows custom Herringbone installations
- Wood Structure surface texture
- Decorative groove edges

- Joint Integrity
- Fade Resistance
- Stain Resistance
- Wear Resistance



ALLOC
TIMBERVIEW
beveled edges



- Features 4-sided beveled edges
- Decorative V-groove appearance
- Wood Structure surface texture
- Available in 4.7" and 6.7" widths

- Joint Integrity
- Fade Resistance
- Stain Resistance
- Wear Resistance



ALLOC
MicrobeVel



- Features small beveled edges on planks 4 sides
- Decorative V-groove appearance
- Wood Structure surface texture
- Made in the USA



- Joint Integrity
- Fade Resistance
- Stain Resistance
- Wear Resistance



Mechanical joint locking system installs in a snap without the need for messy glue.



Alloc Performance Moldings are easy to install and blend perfectly with each design. They have the same fade, stain and wear warranty as our flooring.



Use Alloc's Underlayments for superior thermal insulation, sound reduction, as a moisture barrier and for ease of installation.



Our flooring is easy to maintain using Alloc Free&Clean™.

*U.S. Patent No. 5,706,621; 5,860,267; 6,023,907; 6,182,410; 6,446,405; 6,510,665; 6,516,579

www.alloc.com Toll Free: (877)-DO-ALLOC